

Driving Integration



CL-Amp

Non Invasive A.C. Electrical Current Monitoring Technology,

greatly improving the drive for energy efficiency for legacy data centres.



A purpose built monitoring solution for retrofit, new build and legacy electrical installation monitoring, which enables legacy data centres to be monitored and managed, in order to regain power and cooling capacity, without scheduled power downtime associated with traditional monitoring technologies.

The CL-Amp increases visibility of power demand in a cost effective and efficient 'non-invasive' manner, providing clients far greater control in the ability to identify available capacity, make informed decisions, calculate 'what-if' scenarios, perform risk

analysis and drive down costs, thereby greatly improving the drive for energy efficiency.

An open fork in the CL-Amp enables it to be placed directly over a power cable and a choice of locking-ring collars to suit most international 13A, 16A and 32A cable sizes are provided. Each locking-ring separates into two halves and is placed around the power cable and pushed into the CL-Amp clamping bore, retaining the cable with a neat twist and lock action. A very lightweight device, it is designed to be installed at any convenient location on the cable.

Technical Specification

- Current measuring range 1.0 Ampere to 60 Amperes.
- Measured supply range: 90VAC ~ 250VAC. Frequency: 50Hz ~ 60Hz A.C.
- Size: 134mm x 88.5mm x 41mm, Weight: 135gm
- RS232 / RS485 Communication link to Unite Technology monitoring units: PowerHawk², Hawk-i², Hawk-i³ and Eagle-i. Providing SNMP data collection, monitoring, and configuration of CL-Amp.
- RJ45 connector for direct connection to PowerHawk², Hawk-i³ and Eagle-i unit.
- 12V DC power supply @60mA (typically supplied direct from PowerHawk², Hawk-i², Hawk-i³ and Eagle-i unit).
- Cable collars supplied to support: 8mm, 10mm, 12mm, 13mm, 14mm, 15mm, 16mm & 18mm diameter cables.
- Local LED display provides two digit readout.
- Can be calibrated to cable types to provide typically $\pm 3\%$ accuracy Ampere current readings.

CL-Amp Features

- Uses patented technology for current measurement in the data centre, computer room and PC environments.
- A small compact electrical current meter capable of non-invasively measuring real-time A.C. currents on typical data centre power supply feeds rated up to 32A.
- High quality robust plastic, conforming to international electrical and EMC standards.
- Attachment does NOT require power down of the measured feed.
- CL-Amp appears as a standard PDU input to the PowerHawk², Hawk-i², Hawk-i³ and Eagle-i units for remote monitoring and real time alerting.
- Capable of measuring A.C. electrical currents up to 60A.
- Can be used to bring monitoring functionality to non-intelligent power strips.



COMMERCIAL HEAD OFFICE

Unite Technologies Ltd
Tournament Way
Ashby de la Zouch
Leicestershire
LE65 2UU
Tel +44 (0) 845 271 0130
Email sales@unitetechologies.com

TECHNOLOGY CENTRE

Unite Technologies Ltd
Willow House
Llancayo Court, Usk
Monmouthshire
NP15 1HY
Tel +44 (0) 845 271 0130
Email technical@unitetechologies.com



3 Eghams Court
Boston Drive
Bourne End
Bucks SL8 5YS
United Kingdom
Tel: +44 (0)8707 601 450